



REF.

CLBO 15 TOT4 LED DIM GB UL
CLBO 15 TOT4 LED DIM WB UL

LIGHT SOURCE



120-277V

3 Circuits: 3 Independent Dimmable Circuits. Dimming & Control of the Central Shade, Periferal Shades & Soptlights.

Circuit 1

4 Spotlights 4 GU10 - LED DIM 7 W

Circuit 2

1 TOT4 S LED **Driver:** Constant Current 900mA

LED Integrated:
Led module 350mA

Circuit 3

3 ATA SP	3 Bulbs E26 - LED DIM Globe 15 W
2 MMIK S	2 Bulbs E26 - LED DIM A15 5 W
1 POD SP	1 Bulb E26 - LED DIM A19 10 W
1 POD SM	1 Bulb E26 - LED DIM A19 10 W
1 POPY SP	1 Bulb E26 - LED DIM A19 10 W
4 RDROP SM	4 Bulbs G9 - LED DIM 5 W
2 RDROP SG	2 Bulbs G9 - LED DIM 5 W

MATERIALS & COMPONENTS

15 Wood Veneer Shades
Shade mount required

White Laquered Wood Canopy

6 Ceramic Birds in Gold - GB or White Glaze - WB

Electrical & Steel Cables: The measurements have been calculated for a ceiling height of 11 - 13 ft. If your ceiling is higher let us know so we can adjust your cable lengths.

FINISHES

WOOD VENEER

20 Ivory White

22 Natural Beech

PACKAGING

For freight, please consult our offices

Total Volume: 328,4 ft³

Total Weight: Gross - 1324 Lb | Net -315,5 Lb