



REF.

SKYL M BK/IV LED UL
SKYL M BK/GD LED UL

SKYL M IV/IV LED UL
SKYL M IV/GD LED UL

SKYL M BN/IV LED UL
SKYL M BN/GD LED UL

SKYL M GD/IV LED UL
SKYL M GD/GD LED UL

LIGHT SOURCE



120V: Dimmable

Driver:
Constant Voltage 24V

LED Integrated:
Led module 250mA

2700K / 4000K, CRI90, 8,5W, 50-60Hz

PACKAGING

Box Size: 43 x 31 x 18 cm

Box Volume: 0,023 m³

Weight: Gross - 2,8 Kg | Net - 1,8 Kg

MATERIALS & COMPONENTS

Multimaterial Shade
Wood Veneer, Perforated Metal & Textured Glass

Metal Structure, Perforated Metal & Base

Black Electrical Cable with Dimming Switch: 145 cm

FINISHES

WOOD VENEER

- 20 Ivory White
- 22 Natural Beech

PERFORATED METAL

- IV-Matt Ivory
with Wood Veneer 20
- GD-Gold
with Wood Veneer 22

METAL

- IV-Matt Ivory
- *BN-Black Nickel
- BK-Matt Black
- *GD-Gold

*On Request